GENERAL NOTES:

ANY AREA OUTSIDE COST TO OWNER. LIMIT OF WORK SHALL BE EROSION CONTROL BARRIERS, LIMIT OF GRADING AND SITE PROPERTY LINES INDICATED ON DRAWINGS. THE CONTRACTOR SHALL MAKE ALL NECESSARY CONSTRUCTION NOTIFICATIONS AND APPLY FOR AND OBTAIN ALL NECESSARY CONSTRUCTION PERMITS. THE CONTRACTOR SHALL ALSO PAY ALL FEES AND POST ALL BONDS ASSOCIATED WITH THE SAME AND COORDINATE WITH THE ENGINEER AND ARCHITECT AS REQUIRED. ANY ALTERATION TO THESE DRAWINGS MADE IN THE FIELD DURING CONSTRUCTION SHALL BE RECORDED BY THE CONTRACTOR ON RECORD DOCUMENTS. PORTIONS OF THE ROADWAY, SIDEWALK AND ROADSIDE AREA DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED TO THEIR CONDITIONS PRIOR TO DISTURBANCE. CONTRACTOR SHALL BE SOLELY RESI THE LIMIT OF WORK THAT IS DISTURBED SHALL BE RESTORED TO ITS ORIGINAL CONDITION AT NO ONSIBLE FOR JOB SITE SAFETY AND ALL CONSTRUCTION MEANS AND METHODS AND/OR AS

SITE ELEMENTS TO REMAIN MUST BE PROTECTED FOR DURATION OF PROJECT. CONTRACTOR SHALL **EROSION CONTROL AND SEDIMENTATION NOTES:** ANY SEDIMENT TRACKED ONTO PUBLIC RIGHT-OF-WAYS SHALL BE SWEPT AT THE END OF EACH WORKING MAINTAIN SHALL BE LOCATED WITHIN LIMIT OF WORK LINE AND STABILIZED ALL EROSION CONTROL DURING ENTIRE CONSTRUCTION PERIOD TO PREVENT EROSION

ADDITIONAL EROSION CONTROL MEASURES SHALL BE IMPLEMENTED AS CONDITIONS OWNER OR OWNER'S REPRESENTATIVE. ALL TOPSOIL ENCOUNTERED WITHIN WORK AREA SHALL BE STRIPPED TO ITS FULL DEPTH AND STOCKPILED FOR REUSE EXCESS TOPSOIL SHALL BE DISPOSED OF ON—SITE AS DIRECTED BY OWNER. TOPSOIL PILES SHALL REMAIN SEGREGATED FROM EXCAVATED SUBSURFACE SOIL MATERIALS. ALL AREAS IDENTIFIED AS CRITICAL AREA SEEDING SHALL BE STABILIZED DURING CONSTRUCTION BY SEEDING WITH ANNUAL RYE GRASS AT THE RATE OF FORTY (40) LBS/ACRE. ALL POINTS OF CONSTRUCTION EGRESS OR INGRESS SHALL BE MAINTAINED TO PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC ROADS. WARRANT OR AS DIRECTED BY THE

ADDITIONAL HAYBALES SHALL BE LOCATED AS CONDITIONS WARRANT OR AS DIRECTED BY THE OWNER OR HIS REPRESENTATIVE. AN EROSION CONTROL BARRIER SHALL BE INSTALLED ALONG THE EDGE OF PROPOSED DEVELOPMENT AS INDICATED IN THE PLAN PRIOR TO THE COMMENCEMENT OF DEMOLITION OR CONSTRUCTION OPERATIONS. SOIL EROSION AND SEDIMENTATION CONTROL MEASURES SHALL BE INSPECTED AND MAINTAINED ON A DAILY BASIS DURING CONSTRUCTION TO INSURE THAT CHANNELS, DITCHES AND PIPES ARE CLEAR OF DEBRIS AND THAT THE EROSION CONTROL BARRIERS ARE INTACT. TEMPORARY DIVERSION DITCHES, PERMANENT DITCHES, CHANNELS, EMBANKMENTS AND ANY DWILL BE EXPOSED FOR A PERIOD OF ONE MONTH OR MORE SHALL BE CONSIDERED CRITICAL THESE AREAS SHALL BE MULCHED WITH STRAW. MULCH SHALL BE SPREAD UNIFORMLY IN A OF SUFFICIENT THICKNESS TO COMPLETELY HIDE THE SOIL FROM VIEW. HAYBALE CHECK DAMS SHALL BE PROVIDED AROUND ALL EXISTING DRAIN INLETS PRIOR TO CONSTRUCTION ACTIVITIES AND AROUND ALL PROPOSED DRAIN INLETS PRIOR TO PERMANENT PAVEMENT TO CONTROL SILTATION. Ή BE EXERCISED SO AS TO PREVENT MATERIAL FROM ENTERING DENUDED SURFACE WHIC VEGETATION AREAS. A CONTINUOUS BLANKET THE WETLANDS

CLEAN AND MAINTAIN EROSION CONTROL BARRIER AS REQUIRED DURING CONSTRUCTION OPERATIONS TO ENSURE ITS CONTINUED FUNCTIONALITY. AN EROSION CONTROL BARRIER SHALL BE INSTALLED ALONG THE EDGE OF PROPOSED DEVELOPMENT AS SHOWN ON THE PLAN PRIOR TO THE COMMENCEMENT OF CONSTRUCTION OPERATIONS.

LAYOUT AND MATERIALS NOTES:

ALL LINES AND DIMENSIONS ARE PARALLEL OR PERPENDICULAR TO THE UNLESS OTHERWISE INDICATED. GATES SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURERS LINES THEY ARE

CONTRACTOR SHALL REPORT SIGNIFICANT CONFLICTS TO THE COORDINATE THE LOCATION OF ALL SITE LIGHT STANDARDS WITH IMPROVEMENTS SHOWN ON THESE DRAWINGS. ACCESSIBLE RAMPS SHALL BE PER MASSACHUSETTS STATE ACCESSIBILITY GUIDELINES (WHICHEVER IS MORE STRINGENT). OTECT EXISTING PR OPERTY AND ABUTTING PROPERTIES DURING CONSTRUCTION ACTIVITIES. CODE OWNER AND THE ENGINEER FOR RESOLUTION. AMERICANS WITH

<u>SOFT SURFACE PATH:</u> A. AGGREGATE BASE COURSE SHALL BE COMPACTED GRAVEL BORROW.

SAND AND CRUSHED STONE MIXTURE SHALL CONSIST OF INERT MATERIALS THAT ARE HARD, DURABLE, FREE FROM SURFACE COATINGS AND DELETERIOUS MATERIALS. COLOR SHALL BE GRAY TO BROWN AS BY THE OWNER'S REPRESENTATIVE. GRADATION REQUIREMENTS SHALL BE AS FOLLOWS:

1/2"
100
3/8"
86-100
44
48
56-83
416
430
4200
5-15

ORGANIC BINDER SHALL BE A NATURAL, NON-TOXIC, NON-STAINING, ODORLESS, ENVIRONMENTALLY SAFE POWDER CONSISTING OF 95% PSYLLIUM WITH 70% MUCILLIOD CONTENT. THE POWDER SHALL BE OF A SIZE THAT NOT MORE THAN 10% IS RETAINED ON A U.S. STANDARD #40 MESH SIEVE. THE POWDER BINDER SHALL BE "STABILIZER" AS MANUFACTURED BY STABILIZER, INC., PHOENIX, ARIZONA (1-800-336-2468) OR AN APPROVED EQUAL.

GRADING AND DRAINAGE NOTES:

ALL SITE WORK SHALL MEET OR EXCEED THE SITE WORK SPECIFICATIONS PREPARED FOR THIS PROJECT CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THAT THE PROPOSED IMPROVEMENTS SHOWN ON NOT CONFLICT WITH ANY KNOWN EXISTING OR OTHER PROPOSED IMPROVEMENTS. IF ANY CONFLICTS A THE CONTRACTOR SHALL NOTIFY THE OWNER AND THE ENGINEER PRIOR TO INSTALLATION OF ANY POSITE WORK WHICH WOULD BE AFFECTED. RE COMPILED FROM AVAILABLE RECORD PLANS OF UTE AND ASSUMED. BEFORE COMMENCING SITE WORK CCURATELY LOCATE UNDERGROUND UTILITIES. ANY CONTRACTOR'S RESPONSIBILITY. NO EXCAVATION SHOUTHFIED IN ADVANCE. TILITY COMPANIES AND PUBLIC IN ANY AREA, CONTACT "DIG SAFE" DAMAGE TO EXISTING UTILITIES OR HALL BE DONE UNTIL UTILITY ECT. THE N THE PLANS DO ARE DISCOVERED, PORTION OF THE

ALL DRAINAGE PIPES SHALL BE SMOOTH WALLED EXCEPT WHERE NOTED OTHERWISE. LL WORK PERFORMED AND ALL MATERIALS FURNISHED SHALL CONFORM WITH THE LINES, PECIFIC REQUIREMENTS OR SPECIFICATIONS OF THE CITY OF CAMBRIDGE DPW. CORRUGATED POLYETHYLENE PIPE (ADS N-12 GRADES AND OTHER APPROVED

XISTING SITE DATA IS BASED ON ONE (1) 1"=40' SCALE PLAN DATED, MAY 2005, SC GROUP, INC.

CONTRACTOR SHALL PROTECT ALL UNDERGROUND DRAINAGE, VEHICULAR LOADS DURING CONSTRUCTION. ANY DAMAGE TO OADS WILL BE RESTORED TO ORIGINAL CONDITION.

SEWER AND UTILITY FACILITIES FROM EXCESSIVE THESE FACILITIES RESULTING FROM CONSTRUCTION

DATUM.

ALL SITE CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE MASSACHUSETTS DEPARTMENT OF PUBLIC WORKS (DPW) STANDARD SPECIFICATIONS FOR HIGHWAYS AND BRIDGES, AND THE CITY OF CAMBRIDGE PUBLIC WORKS. ALL SITE WORK SHALL BE IN CONFORMANCE WITH THE CITY OF CAMBRIDGE CONSERVATION COMMISSION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE LEGAL REMOVAL AND AS MAY BE DIRECTED BY THE A/E. AND DISPOSAL 유 ALL DEBRIS FROM THE SITE

ALL SITE WORK SHALL MEET OR EXCEED THE SITE WORK SPECIFICATIONS DATED XXPROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THAT THE PROTHE PLANS DO NOT CONFLICT WITH ANY KNOWN EXISTING OR OTHER PROPOSED IMPARE DISCOVERED, THE CONTRACTOR SHALL NOTIFY THE OWNER AND THE ENGINEER PORTION OF THE SITE WORK WHICH WOULD BE AFFECTED.

REQUIREMENTS OR SPECIFICATIONS OF THE CITY OF CAMBRIDGE DPW. ING OR PAVEMENT ABUTS NEW CONSTRUCTION, THE EDGE OF THE EXIST TO A CLEAN, SMOOTH EDGE. BLEND NEW PAVEMENT, CURBS AND MATCHING LINES, GRADES AND JOINTS. PITCH EVENLY BETWEEN SPOT

THE CONTRACTOR SHALL VERIFY EXISTING THE ENGINEER UTILITY COVERS, GRATES, ETC. SHALL BE ADJUSTED JERWISE NOTED. GRADES IN THE FIELD AND REPORT ANY TO BE FLUSH WITH THE PAVEMENT FINISH IMMEDIATELY TO GRADE UNLESS

PITCH EVENLY BETWEEN SPOT GRADES. ALL PAVED AREAS MUST PITCH TO DRAIN AT A MINIMUM JNLESS SPECIFIED. ANY DISCREPANCIES NOT ALLOWING THIS MINIMUM PITCH SHALL BE REPORTED PRIOR TO CONTINUING WORK. THE CONTRACTOR SHALL REMOVE ALL EROSION CONTROL BARRIERS AFTER REVEGETATION AFTER APPROVAL OF THE CONSERVATION COMMISSION AND WETLAND SPECIALIST. WETLANDS ARE TO REMAIN SED. NO ENCROACHMENT PERMITTED DISTURBED AND

THE CONTRACTOR SHALL SCHEDULE HIS WORK TO ALLOW THE FINISHED SUBGI WITHOUT PUDDLING. SPECIFICALLY, ALLOW WATER TO ESCAPE WHERE PROPOS APPLICATION OF THE FINISH SUBGRADE AND/OR SURFACE PAVING. PROVIDE REQUIRED. RADE ELEVATIONS TO DRAIN PROPERLY SED CURB MAY RETAIN RUNOFF PRIOR TEMPORARY POSITIVE DRAINAGE AS

ABANDON EXISTING UTILITY SERVICES ON—SITE ACCORDING TO UTILITY COMPANY AND CITY REQUIREMENTS. CAMBRIDGE

CAVATION REQUIRED WITHIN THE PROXIMITY OF ALL REPAIR ANY DAMAGE TO EXISTING UTILITY ERATIONS AT NO COST TO THE OWNER. UTILITIES MUST BE LOCATED ON SITE BY CONTRACTOR PRIOR TO COMMENCING WORK. ABANDON, CAP AND OTHERWISE DISCONNECT SERVICES AS REQUIRED BY UTILITY COMPANIES WITHIN JURISDICTION. CALL DIG-SAF VERIFY LOCATIONS. EXISTING UTILITY LINES SHALL BE DONE BY HAND. LINES OR STRUCTURES INCURRED DURING CONSTRU

UTILITY INSTALLATION ₩ H CITY OF UTILITY DEPARTMENTS.

VERTICAL GRANITE CURB	BITUMINOUS CONCRETE BERM	BUILDING	TREE LINE	TREE	SIGN	STONE WALL	SOFT SURFACE PATH	BITUMINOUS CONCRETE	CONCRETE	CHAIN LINK FENCE	BOLLARD / BOLLARD LIGHT	OVERHEAD WIRE	GUY WIRE	UTILITY POLE	LIGHT POLE	ELECTRIC MANHOLE	TELEPHONE MANHOLE	UNDERGROUND ELECTRIC AND TELEPHONE	UNDERGROUND TELEPHONE	UNDERGROUND ELECTRIC	UNDERGROUND GASLINE	SEWERLINE/SEWER MANHOLE	WATERINE	REINFORCED CONCRETE PIPE	CATCH BASIN	DRAINLINE/DRAIN MANHOLE	BOUNDARY OF BORDERING VEGETATED WETLAND	SPOT ELEVATION	INDEX CONTOUR	INTERMEDIATE CONTOUR		LEGEND:
				*	•	000000000000000000000000000000000000000				× × ×			¢	¢	¤	0	0		7	E		SSS			 	DDMH	#F-B10	125X4		124	EXISTING	
VGC				→	· }			BIT. CONC.	CONC	CLF	₩	WHO	GW	UP	LP	EMH	TMH	Е&Т	Т	Ш	G	S		RCP RCP		DMH		× 125.4	(210)	124	PROPOSED	

PLA! NTING AND LIGHTING NOTES:

VERIFY ALL EXISTING UTILITY LINES PRIOR TO PLANTING AND REPORT ANY CONFLICTS TO THE OWNER OR HIS REPRESENTATIVE. ALL PLANT MATERIAL SHALL CONFORM TO THE MINIMUM GUIDELINES ESTABLISHED BY THE AMERICAN STANDARD FOR NURSERY STOCK PUBLISHED BY THE AMERICAN ASSOCIATION OF NURSERYMEN, INC. ANY PROPOSED SUBSTITUTIONS OF PLANT MATERIAL SHALL BE MADE WITH MATERIAL EQUIVALENT TO THE DESIRED MATERIAL IN OVERALL FORM, HEIGHT, BRANCHING HABIT, FLOWER, LEAF, COLOR, FRUIT AND CULTURE. PROPOSED SUBSTITUTIONS WILL ONLY BE CONSIDERED IF SUBMITTED WITH ENUMERATED REASONS WHY SUBSTITUTIONS ARE PROPOSED.

PLANT ALL PL, NO PLANT SHALL BE PLANTED BEFORE ACCEPTANCE OF ROUGH GRADING. OAM AND SEED ALL DISTURBED AREAS UNLESS OTHERWISE INDICATED. MATERIALS SHALL BEAR SAME RELATIONSHIP TO GRADE AS THEY BORE TO GRADE IN THE NURSERY. ANT MATERIALS SHALL BE GUARANTEED FOR ONE YEAR FOLLOWING DATE OF FINAL ACCEPTANCE.

DIMENSIONS FOR LIGHT LOCATIONS ARE TO THE CENTER OF MOUNTING POLES. REGRADE STOCKPILE AREA AFTER REMOVAL OF SURPLUS MATERIALS (SEE SITE WORK SPECIFICATIONS). LOAM AND SEED THE DISTURBED AREA.

CUTOFF ALL LIGHT MOUNTING POLES SHALL BE LOCATED AT A MINIMUM OF TWO FEET, SIX INCHES (2'—6") FROM EDGE OF WALKWAY. POLES SHALL BE FLUSH WITH GRADE UNLESS OTHERWISE NOTED. OPSOIL STRIPPED FROM THE SITE AND PROPERLY STOCKPILED PRIOR TO APPLICATION MAY, UPON APPROVAL OF THE NGINEER, BE USED FOR PREPARATION OF LAWNS AND PLANTING BEDS. IT SHOULD BE FREE OF LARGE (ONE (1) NICH OR GREATER) COBBLES, ROOTS, OLD SOD, TRASH, WOOD OR OTHER CONTAMINANTS AND BE OF A FRIABLE CONSISTENCY AND SUITABLE FOR PLANT GROWTH. FIXTURES WILL BE UTILIZED TO ENSURE NO OFF-SITE GLARE IS CREATED.

THE LANDSCAPE CONTRACTOR SHALL FURNISH TOPSOIL. TOPSOIL SHALL BE FERTILE, FRIABLE, NATURAL AND PRODUCTIVE TOPSOIL OF GOOD CLAY—LOAM TYPE. IT SHALL BE FREE OF WEED SEEDS. TOPSOIL SHALL BE WITHOUT ADMIXTURE OF SUBSOIL AND SHALL BE REASONABLY FREE OF STONES, LUMPS, ROOTS, STICKS AND OTHER FOREIGN MATTER. TOPSOIL SHALL NOT BE WORKED OR APPLIED IN A MUDDY OR WET CONDITION.

PEAT AND ORGANIC MATERIAL STRIPPED FROM AN ALTERED WETLAND IS TO BE PROPERLY STOCKPILED AND USED FOR PREPARATION OF PROPOSED WETLAND AREA. WETLAND SEED SHALL BE FRESH, RECLEANED SEED OF THE LATEST CROP. WETLAND SEED SHALL BE DELIVERED TO THE SITE IN THE ORIGINAL CONTAINERS WHICH SHALL BEAR THE VENDOR'S GUARANTEE OF ANALYSIS.

REMOVE TOPSOIL AREAS I SUBGRA CALLED) 10—10—10 FERTILIZER AT A RATE OF TWENTY—TWO (22) POUNDS PER ONE THOUSAND (1,000) SQUARE FEET CORPORATE INTO THE SOIL UNIFORMLY. L SHALL BE SPREAD TO A MINIMUM DEPTH OF FOUR (4) INCHES AFTER SETTING ON ALL STRIPPED PLANTED INCLUDING SLOPE STABILIZATION, LAWN AREAS AND PLANTING BEDS AFTER FILLS ARE PROPERLY SETTLED AND ADE HAS BEEN APPROVED BY THE OWNER. THE SETTLED TOPSOIL SHALL BE UP TO THE FINISHED GRADE AS FOR ON THE DRAWINGS. SCARIFY SUBGRADE TO A DEPTH OF TWO (2) INCHES BEFORE PLACING TOPSOIL. ALL ROCKS AND DEBRIS FROM SOIL SURFACE AND GRADE TO AN EVEN SURFACE.

APPLY AREAS SPREAD AND INC PLANTING SEED SHALL BE SOWN IN SEASONAL CONDITIONS AS APPROPRIATE FOR GOOD SEED SURVIVAL, OR AT SUCH IMES AS APPROVED BY THE OWNER. PROVIDE SUFFICIENT HOSE AND SPRINKLER HEADS FOR ADEQUATE WATERING O MAINTAIN A MOIST SEED BED AT ALL TIMES. DOLOMITIC LIME AT THE RATE OF ONE HUNDRED (100) POUNDS PER ONE THOUSAND (1,000) SQUARE FEET THE BEING PREPARED FOR PLANTING.

AFTER WITH A STRAW MULCH SHALL BE SPREAD UNIFORMLY OVER ALL SEEDED AREAS AT THE RATE OF TWO (2) BALES PER ONE THOUSAND (1,000) SQUARE FEET. WATER, MULCH AND SEED BED THOROUGHLY AND IMMEDIATELY AFTER COMPLETION OF MULCHING. SOIL SHALL BE MOISTENED TO A DEPTH OF FOUR (4) INCHES. CONTRACTOR SHALL INSTRUCT OWNERS REPRESENTATIVE ON APPROPRIATE WATERING PROCEDURES DURING INITIAL ESTABLISHMENT. PLANTING SEED SHALL BE SOWN EVENLY WITH MECHANICAL SPREADER OR BY HAND AT THE RATE OF SIX (6) POUNDS PER ONE THOUSAND (1,000) SQUARE FEET. ALL SEEDING SHALL BE DONE ON DAYS WHEN THE WIND DOES NOT EXCEED A VELOCITY OF FIVE (5) MILES PER HOUR AND THE SEED SHALL BE DRY. SEEDING, THE SURFACE OF THE SOIL SHALL BE EVENLY RAKED WITH A FINE—TOOTHED RAKE AND THEN ROLLED HAND ROLLER WEIGHING NOT LESS THAN ONE HUNDRED (100) POUNDS PER FOOT OF WIDTH.

REPAIR TOLERA PROTECT NEWLY TOPSOILED, GRADED AND/OR SEEDED AREAS FROM TRAFFIC AND EROSION. KEEP AREAS FREE OF TRASH AND DEBRIS RESULTING FROM LANDSCAPE CONTRACTOR OPERATIONS. THE LANDSCAPE CONTRACTOR IS TO CLEAN UP AND REMOVE ANY DEBRIS FROM THE SITE CAUSED BY THE ANDSCAPE CONTRACTOR. AND RE-ESTABLISH GRADES IN SETTLED, ERODED AND RUTTED AREAS TO THE SPECIFIED GRADE AND NCES. WARNING SIGNS IN SEEDED AREAS AND ERECT NECESSARY BARRICADES TO PREVENT DAMAGE BY PERSONS OR IES AND MAINTAIN THESE FOR AT LEAST THIRTY (30) DAYS. AIN OF THE LAWN AREAS DO NOT SHOW A PROMPT "CATCH", THESE SHALL BE RESEEDED AT THE SAME RATE THE SAME MANNER AS BEFORE IN INTERVALS OF TEN (10) DAYS, WHICH PROCESS SHALL CONTINUE UNTIL A OF GRASS IS ESTABLISHED OVER THE ENTIRE AREA.

THE A/E RESERVES THE RIGHT TO ADJUST FINAL GRADES IN THE FIELD TO SAVE EXISTING VEGETATION. PROVIDE 6" LOAM AND SEED ON ALL DISTURBED AREAS UNLESS NOTED OTHERWISE. PLANT MATERIAL IS TO BE MAINTAINED BY THE LANDSCAPE CONTRACTOR WHILE THE PROJECT IS UNDERWAY. ALL TREES ALONG SIDEWALKS SHALL HAVE A MINIMUM SIX (6) FOOT BRANCHING HEIGHT. THE CONTRACTOR SHALL TAKE ALL MEASURES NECESSARY TO PROTECT EXISTING VEGETATION THAT IS TAGGED BY THE A/E, "TO BE SAVED". ALL TREES TO BE SAVED SHALL BE PROTECTED WITH A SNOW FENCE AND HAY BALES CIRCLING THE TREE AT A MINIMUM DISTANCE OF 1/2 THE CANOPY. ALL TREES NOTED FOR CLEARING AND SELECTIVE PRUNING AND THINING SHALL BE EXECUTED BY A LICENSED ARBORIST. THE CONTRACTOR SHALL CLEARLY MARK LIMITS OF CLEARING AND LIMITS OF SELECTIVE PRUNING AND THINING, FOR REVIEW BY THE A/E PRIOR TO ANY CLEARING OPERATIONS.

PLANT QUANTITIES NOTED IN THE PLANT SCHEDULE ARE APPROXIMATE AND ARE PROVIDED FOR THE CONVENIENCE OF THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE FURNISHING AND INSTALLATION OF ALL PLANT MATERIALS NOTED ON THE PLANTING PLAN.

ADDREVIATIONS:
DESCRIPTION
BALLED AND BURLAPPED
CALIPER
HEIGHT
QUANTITY
RADIUS
TYPICAL
VERIEY IN FIELD
: - - - - - -



0

DCR NOTES

H:\FDA\PFA Project Data\123-1001.00\dwg\1231001_00_DCR.dwg Plotted on: Sep. 29, 2005 @ 9:09a



